

# MR<sup>®</sup> 70 AMS Developer White



## Product characteristics

- Developer for penetrant testing acc. to EN ISO 3452
- Carrier medium solvent
- Very easy removable from the surface
- Quick-drying
- Spray distance of about 20 cm
- QPL SAE AMS 2644 for fluorescent testing

## Minimum shelf life / Temperatures

Aerosol / Bulk:

3 years at storage temperature

Storage: + 5 °C - + 45 °C

Application: - 10 °C - + 50 °C and  
- 30 °C - + 50 °C

(with MR<sup>®</sup> 312, MR<sup>®</sup> 79, MR<sup>®</sup> 85 or MR<sup>®</sup> 88)



## Approvals / Specification

- EN ISO 3452-2
- EN ISO 3452-6
- ASTM E165
- ASME Code V, Art. 6
- JIS 2343-2
- AMS 2644
- VDA236-150
- EN ISO 3452-5
- RCC-M
- PMUC
- TLV 9017  
01:2011-01
- ASTM E1417
- QPL SAE AMS 2644




## Further information

Process description according to EN ISO 3452-1 on request or on [www.mr-chemie.de/en](http://www.mr-chemie.de/en). For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

## Suggested products

Pre-cleaner: MR<sup>®</sup> 71, MR<sup>®</sup> 79, MR<sup>®</sup> 85 MR<sup>®</sup> 88, MR<sup>®</sup> 3002  
Penetrant: for all penetrant typ I, II & III (not for System Hot)  
Remover: MR<sup>®</sup> 79, MR<sup>®</sup> 85, MR<sup>®</sup> 88, Water  
Test block: Reference-Testblock 1 and 2, ASTM Testblock

## Delivery form



\*\*Technical changes reserved!\*\*